



1675 MacArthur Blvd., Costa Mesa, CA, 92626 USA

Main Number (714) 754-6175 Sales & Marketing (714) 957-7100 or toll free (USA only) (800) 854-4079

Customer Service(714) 957-7150 or toll free (USA only) (800) 772-2834

AD-S282H, AD-S282HT, and I-282H Weather Resistant Multi-Use Loudspeakers

IMPORTANT SAFETY PRECAUTIONS

- 1- Read these instructions.
- 2- Keep these instructions.
- 3- Heed all warnings.
- 4- Follow all instructions.
- 5- Install in accordance with QSC Audio Product's instructions and a licensed, professional engineer.
- 6- Refer all servicing to qualified personnel. Servicing is required when the apparatus has been damaged in any way.



WARNING!

Do not use this loudspeaker in "stand alone" or free-standing applications set on its bottom. It could fall and cause injury or death.

Before placing, installing, rigging, or suspending any speaker product, inspect all hardware, suspension, cabinets, transducers, brackets and associated equipment for damage. Any missing, corroded, deformed or non-load rated component could significantly reduce the strength of the installation, placement, or array. Any such condition severely reduces the safety of the installation and should be immediately corrected. Use only hardware which is rated for the loading conditions of the installation and any possible short-term unexpected overloading. Never exceed the rating of the hardware or equipment. **Consult a licensed, professional engineer when any doubt or questions arise regarding a physical equipment installation.**

Ensure a safety cable is securely attached to the loudspeaker and to a suitable retaining point to restrain the loudspeaker from falling in the event of a primary mounting failure. The cable, its securing hardware, and the retaining point must be able to support many times the loudspeaker's weight in the event it should fall. **Consult a licensed, professional engineer should any doubt of question arise regarding the physical installation of this loudspeaker.**

Mount this loudspeaker in accordance with the provided instructions.

Ensure the loudspeaker is properly and securely mounted.

AD-S282H and AD-S282HT: Use this loudspeaker only properly and securely mounted using the included yoke mount or suitable OmniMount®.

I-282H: Use this loudspeaker properly and securely mounted on a 1.375" or 1.500" (35 or 38mm) diameter loudspeaker pole mount, the included yoke mount, or suitable OminMount.

© Copyright 2004, QSC Audio Products, Inc.

QSC® is a registered trademark of QSC Audio Products, Inc.

"QSC" and the QSC logo are registered with the U.S. Patent and Trademark Office

OmniMount® is a registered trademark of OmniMount Systems, Phoenix, AZ, USA

